


Product Type: Plug-in terminal-Plug

Product Name:MC-RU3.81SV09-F-0001

Product Description: Pitch:3.81mm Rated Voltage : 160V Rated Current:8A colour : customizable

Product Size



Parameters

| | |
|-------------------------|----------------------|
| ⌘ SUPU ID | MC-RU3.81SV09-F-0001 |
| ⌘ Pitch | 3.81 |
| ⌘ Number of connections | 9 |
| ⌘ Connection method | - |

| | |
|-------------------------------|----------------------------------|
| ☞ Protection Level | IP20 |
| ☞ Operating temperature range | -40~+105°C |
| ☞ Insulation material | PA66 |
| ☞ Insulation material group | I |
| ☞ Contact material | Copper alloy |
| ☞ Contact plating | Sn,Plated |
| ☞ Color | Green/Black/Blue/Grey/Orange/Red |

Technical data

| | |
|---|-----------------|
| ☞ IEC Rated Current | 8A |
| ☞ IEC Rated Voltage | 160V |
| ☞ Overvoltage category | III/III/ II |
| ☞ Degree of pollution | 3 2 2 |
| ☞ Rated impulse voltage | 2.5KV2.5KV2.5KV |
| ☞ UL Rated Current | 8A - 8A |
| ☞ UL Rated Voltage | 300V - 300V |
| ☞ Conductor cross section rigid | - |
| ☞ Conductor cross section flexible | - |
| ☞ Conductor cross section flexible,with furrule | - |
| ☞ Locking screw Specification | - |
| ☞ Locking screw torque | - |
| ☞ Fixed Screw Specification | M2.5 |
| ☞ Stripping length | - |
| ☞ Use group | B/C/D |

☞ Order No

MC-RU3.81SV09-F-0001

Ningbo SUPU Electronics Co., Ltd.

Address: No. 150, Xinxing 4th Road, High-tech Industrial Development Zone,
Cixi City, Zhejiang Province, China

Zip code: 315303

Switchboard: +86 574-63288158

Fax: +86 574-63288170

E-mail:supucontact@supu.cn

Service Hotline: 400-626-6336



Wechat

Date:2025-08-30 10:00

The right to modify data belongs to SUPU.