




Product Type: Barrier terminal

Product Name:SCR-OP-
24DC48DC-3A

Product Description: Optocoupler relay IN:24VDC
OUT:48VDC-3A

Parameters

⌘ SUPU ID	SCR-OP-24DC48DC-3A
⌘ Pitch	SCR Series
⌘ Number of levels	EN61947-5-1:2017/AC:2020
⌘ Number of connections	DIN 35mm rail mounting
⌘ Connection method	No spacing arrangement
⌘ Protection Level	NPN / PNP
⌘ Operating temperature range	Push-in PT
⌘ Insulation material	26-12/0.2-2.5mm ²
⌘ Insulation material group	4KV
⌘ Contact material	6.2x90x72
⌘ Contact plating	PA66

Technical data

⌘ IEC Rated Current	C5191
---------------------	-------

⌘ IEC Rated Voltage	Tin
⌘ Overvoltage category	V0
⌘ Degree of pollution	-40°C~+80°C
⌘ Rated impulse voltage	15~50mA
⌘ Conductor cross section rigid	Emerald (LED)
⌘ Stripping length	10~200HZ*
⌘ Tightening torque	48VDC
⌘ Connection capacity AWG	100mA~3000mA
⌘ UL Rated Current	Anti-reverse protection, TVS surge protection
⌘ UL Rated Current	5~48VDC

Commercial data

⌘ Order No	SCR-OP-24DC48DC-3A
⌘ Packing unit	PCS
⌘ Minimum order quantity	10

Ningbo SUPU Electronics Co., Ltd.

Address: No. 150, Xinxing 4th Road, High-tech Industrial Development Zone,

Cixi City, Zhejiang Province, China

Zip code: 315303

Switchboard: +86 574-63288158

Fax: +86 574-63288170

E-mail:supucontact@supu.cn

Service Hotline: 400-626-6336



Wechat

Date:2026-02-18 14:05

The right to modify data belongs to SUPU.