





Product Type: Screw terminal

Product Name:316991

Product Description: Connection method:Screw connection,IEC Rated current:76A,IEC Rated Voltage:800V,Number of connections:2,Number of levels : 1,Rated cross section:10-4AWG

Product Size



Parameters

⌘ SUPU ID	316991
⌘ Width	12.2mm
⌘ Number of levels	1
⌘ Number of connections	2
⌘ Connection method	Screw connection
⌘ Protection Level	IP20
⌘ Insulation material	PA66
⌘ Insulation material group	I

☞ Contact material	Copper
☞ Contact plating	Sn,Plated
☞ Ambient temperature (operation)	-40℃~105℃
☞ Ambient temperature (assembly)	-5℃~70℃
☞ Ambient temperature (storage)	-25℃~60℃
☞ Permissible humidity (storage/transport)	30%~70%
☞ Product type	Terminal block of side-entry

Technical data

☞ IEC Rated Current	76A
☞ IEC Rated Voltage	800V
☞ Overvoltage category	III
☞ Degree of pollution	3
☞ Rated impulse voltage	8kV
☞ UL Rated Current	85A
☞ UL Rated Voltage	600V
☞ Conductor cross section rigid	6-16mm ²
☞ Conductor cross section flexible	6-16mm ²
☞ Conductor cross section flexible,with furrule	6-16mm ²
☞ Locking screw Specification	M5
☞ Locking screw torque	2.0-2.5N.m
☞ Fixed Screw Specification	/
☞ 固定螺钉扭矩	/
☞ Stripping length	12-13mm

☞ Use group	B/C
☞ Rated cross section	10-4AWG
☞ UL Rated Current	85A
☞ UL Rated Current	600V

Commercial data

☞ Order No	316991
------------	--------

Ningbo SUPU Electronics Co., Ltd.

Address: No. 150, Xinxing 4th Road, High-tech Industrial Development Zone,
Cixi City, Zhejiang Province, China

Zip code: 315303

Switchboard: +86 574-63288158

Fax: +86 574-63288170

E-mail:supucontact@supu.cn

Service Hotline: 400-626-6336



Wechat