







Product Type: Slim intermediate relay

Product Name: SCR-RP-24DC-1C

Product Description: Slim relay, Push-In

Type, Compact, 1C/O, Input Voltage 24VDC

Product Size



Parameters

⌘ SUPU ID	SCR-RP-24DC-1C
⌘ Protection Level	IP20
⌘ Ambient temperature (operation)	-40~+85°C

☞ Ambient temperature (storage)	-40~+85°C
☞ Mounting Type	DIN 35 rail mounting
☞ Contact material	silver alloy
☞ Connection method	Push-in type
☞ Contact connection type	1C

Technical data

☞ IEC Rated Voltage	24VDC
☞ Dielectric withstand voltage	4000VAC 1min : Coils/ contacts 1000VAC 1min : BetweenContacts
☞ Endurance	Mechanical: 10 million times or more Electrical: Normally open type more than 60,000 times (high temperature 85 °C, 1 s on 9s off) Switching type 30,000 times or more (high temperature 85 °C, 1 s on 9s off)
☞ Operating voltage	≤75% of rated voltage
☞ Release Voltage	≥10% of rated voltage
☞ Maximum permissible voltage	110% of rated voltage
☞ Nominal power consumption	About 0.17W
☞ Response time	8ms or less
☞ Release time	4ms or less
☞ Protective circuit	None
☞ Status display	visual
☞ Maximum switching power	1500VA/180W
☞ Rated load capacity	AC277V/6A DC30V/6A
☞ Rated load current	6A
☞ Insulation resistance	1000MΩ

Commercial data

☞ Order No	SCR-RP-24DC-1C
☞ Packing unit	PCS
☞ Minimum order quantity	10
☞ Single piece weight	26g

Ningbo SUPU Electronics Co., Ltd.

Address: No. 150, Xinxing 4th Road, High-tech Industrial Development Zone,
Cixi City, Zhejiang Province, China
Zip code: 315303
Switchboard: +86 574-63288158
Fax: +86 574-63288170
E-mail:supucontact@supu.cn
Service Hotline: 400-626-6336



Wechat