




Product Type: Barrier terminal

Product Name: TBR80-08C-LR-001

Product Description: pitch : 19.0mm, rated voltage UL600V, rated current UL80A, color: black, Rated cross section 20-4AWG

Product Size



Parameters

 SUPU ID	TBR80-08C-LR-001
 Pitch	19
 Number of levels	single layer
 Number of connections	16

☞ Connection method	Screw connection
☞ Protection Level	IP20
☞ Operating temperature range	-40°C ~+125°C
☞ Insulation material	PC
☞ Insulation material group	III
☞ Contact material	Copper alloy
☞ Contact plating	Sn plated

Technical data

☞ IEC Rated Current	101/101/101
☞ IEC Rated Voltage	800/1000/1000
☞ Overvoltage category	III/III/ II
☞ Degree of pollution	3/2/2
☞ Rated impulse voltage	/
☞ Conductor cross section rigid	0.5-25
☞ Stripping length	13-14
☞ Tightening torque	22.15
☞ Connection capacity AWG	20-4
☞ UL Rated Current	80/80/5
☞ UL Rated Current	600/600/600

Commercial data

☞ Order No	TBR80-08C-LR-001
------------	------------------

Ningbo SUPU Electronics Co., Ltd.

Address: No. 150, Xinxing 4th Road, High-tech Industrial Development Zone,
Cixi City, Zhejiang Province, China

Zip code: 315303

Switchboard: +86 574-63288158

Fax: +86 574-63288170

E-mail:supucontact@supu.cn

Service Hotline: 400-626-6336



Wechat

Date:2025-07-21 09:08

The right to modify data belongs to SUPU.