





Product Type: Barrier terminal

Product Name:TBR100-01P-GR-0002

Product Description: rated voltage UL600V, rated current UL100A,color: black, Rated cross section 16-2AWG

Product Size



Parameters

 SUPU ID	TBR100-01P-GR-0002
 Pitch	-
 Number of levels	single layer
 Number of connections	2

☞ Connection method	Screw connection
☞ Protection Level	IP20
☞ Operating temperature range	-40°C ~+125°C
☞ Insulation material	PC
☞ Insulation material group	III
☞ Contact material	Copper alloy
☞ Contact plating	Sn plated

Technical data

☞ IEC Rated Current	/
☞ IEC Rated Voltage	/
☞ Overvoltage category	III/III/ II
☞ Degree of pollution	3/2/2
☞ Rated impulse voltage	/
☞ Conductor cross section rigid	-
☞ Stripping length	16-17
☞ Tightening torque	40
☞ Connection capacity AWG	16-2
☞ UL Rated Current	100/100/5
☞ UL Rated Current	600/600/600

Commercial data

☞ Order No	TBR100-01P-GR-0002
------------	--------------------

Ningbo SUPU Electronics Co., Ltd.

Address: No. 150, Xinxing 4th Road, High-tech Industrial Development Zone,
Cixi City, Zhejiang Province, China

Zip code: 315303

Switchboard: +86 574-63288158

Fax: +86 574-63288170

E-mail:supucontact@supu.cn

Service Hotline: 400-626-6336



Wechat

Date:2025-07-16 13:32

The right to modify data belongs to SUPU.