





Product Type: Plug-in terminal-Socket

Product Name:425412

Product Description: Pitch:2.5mm Rated
Voltage : 160V Rated Current:4A Connection
method : Spring cage connection colour : White
Grey

Product Size



Parameters

 SUPU ID	425412
 Pitch	2.5
 Number of levels	Single layer
 Number of connections	12

☞ Connection method	Spring cage connection
☞ Protection Level	IP20
☞ Operating temperature range	-40~+105°C
☞ Insulation material	PA66
☞ Insulation material group	I
☞ Contact material	Copper alloy
☞ Contact plating	Sn,Plated
☞ Color	白灰色

Technical data

☞ IEC Rated Current	160V
☞ IEC Rated Voltage	4A
☞ Overvoltage category	- III II
☞ Degree of pollution	3 2 2
☞ Rated impulse voltage	- 2.5KV 2.5KV
☞ UL Rated Current	5A - 5A
☞ UL Rated Voltage	150V - 300V
☞ Conductor cross section rigid	0.2-0.5mm ²
☞ Conductor cross section flexible	0.2-0.5mm ²
☞ Conductor cross section flexible,with furrule	0.2-0.5mm ²
☞ Locking screw Specification	-
☞ Locking screw torque	-
☞ Fixed Screw Specification	-
☞ 固定螺钉扭矩	-

☞ Stripping length	5-6mm
☞ Use group	B/C/D
☞ Rated cross section	28-20AWG

Commercial data

☞ Order No	425412
------------	--------

Ningbo SUPU Electronics Co., Ltd.

Address: No. 150, Xinxing 4th Road, High-tech Industrial Development Zone,

Cixi City, Zhejiang Province, China

Zip code: 315303

Switchboard: +86 574-63288158

Fax: +86 574-63288170

E-mail:supucontact@supu.cn

Service Hotline: 400-626-6336



Wechat