





Product Type: Plug-in terminal-Socket

Product Name:450214-04D

Product Description: Pitch:5.0mm Rated

Voltage : 320V Rated Current:12A colour : grey

## Product Size



## Parameters

|                         |              |
|-------------------------|--------------|
| ⌘ SUPU ID               | 450214-04D   |
| ⌘ Pitch                 | 5            |
| ⌘ Number of levels      | Single layer |
| ⌘ Number of connections | 14           |

|                               |              |
|-------------------------------|--------------|
| ☞ Connection method           | -            |
| ☞ Protection Level            | IP20         |
| ☞ Operating temperature range | -40~+105°C   |
| ☞ Insulation material         | PA66         |
| ☞ Insulation material group   | I            |
| ☞ Contact material            | Copper alloy |
| ☞ Contact plating             | Sn,Plated    |
| ☞ Color                       | Grey         |

## Technical data

|                                                 |                   |
|-------------------------------------------------|-------------------|
| ☞ IEC Rated Current                             | 320V              |
| ☞ IEC Rated Voltage                             | 12A               |
| ☞ Overvoltage category                          | III III II        |
| ☞ Degree of pollution                           | 3 2 2             |
| ☞ Rated impulse voltage                         | 4.0KV 4.0KV 4.0KV |
| ☞ UL Rated Current                              | 15A - 10A         |
| ☞ UL Rated Voltage                              | 300V - 300V       |
| ☞ Conductor cross section rigid                 | -                 |
| ☞ Conductor cross section flexible              | -                 |
| ☞ Conductor cross section flexible,with furrule | -                 |
| ☞ Locking screw Specification                   | -                 |
| ☞ Locking screw torque                          | -                 |
| ☞ Fixed Screw Specification                     | -                 |
| ☞ 固定螺钉扭矩                                        | -                 |

|                       |       |
|-----------------------|-------|
| ☞ Stripping length    | -     |
| ☞ Use group           | B/C/D |
| ☞ Rated cross section | -     |

|                 |            |
|-----------------|------------|
| Commercial data |            |
| ☞ Order No      | 450214-04D |

Ningbo SUPU Electronics Co., Ltd.

Address: No. 150, Xinxing 4th Road, High-tech Industrial Development Zone,  
Cixi City, Zhejiang Province, China

Zip code: 315303

Switchboard: +86 574-63288158

Fax: +86 574-63288170

E-mail:supucontact@supu.cn

Service Hotline: 400-626-6336



Wechat