


Product Name:MC-PA7.5H14-F-0002



Technical drawing of the PCB layout for the 4-channel relay module. The drawing includes three views: a side profile, a top view, and a bottom view.

Side Profile View:

- Overall height: 3.50 ± 0.30 mm
- Base width: 12.00 mm
- Mounting tab width: 2.00 mm
- Mounting hole diameter: 1.00 mm
- Pin pitch: 7.50 mm

Top View:

- Overall width: 18.00 mm
- Mounting hole diameter: 1.00 mm
- Pin pitch: 7.50 mm
- Dimension $a = 7.50 \times (P-1)$
- Dimension $b = 7.50 \times (P-1) + 18.00$

Bottom View:

- Overall width: 12.00 mm
- Mounting hole diameter: 1.40 mm
- Pin pitch: 7.50 mm
- Dimension $a = 7.50 \times (P-1)$
- Dimension $b = 7.50 \times (P-1) + 18.00$

SUPU ID	MC-PA7.5H14-F-0002
Pitch	7.5
Number of levels	Single layer
Number of connections	14

☞ Connection method	-
☞ Protection Level	IP20
☞ Operating temperature range	-40~+105°C
☞ Insulation material	PA66
☞ Insulation material group	I
☞ Contact material	Copper alloy
☞ Contact plating	Sn,Plated
☞ Color	Green/Black/Blue/Grey/Orange/Red

Technical data

☞ IEC Rated Current	630V
☞ IEC Rated Voltage	18A
☞ Overvoltage category	III III II
☞ Degree of pollution	3 2 2
☞ Rated impulse voltage	6.0KV 6.0KV 6.0KV
☞ UL Rated Current	15A - 10A
☞ UL Rated Voltage	300V - 300V
☞ Conductor cross section rigid	-
☞ Conductor cross section flexible	-
☞ Conductor cross section flexible,with furrule	-
☞ Locking screw Specification	-
☞ Locking screw torque	-
☞ Fixed Screw Specification	-
☞ 固定螺钉扭矩	-

☞ Stripping length	-
☞ Use group	B/C/D
☞ Rated cross section	-

Commercial data

☞ Order No	MC-PA7.5H14-F-0002
------------	--------------------

Ningbo SUPU Electronics Co., Ltd.

Address: No. 150, Xinxing 4th Road, High-tech Industrial Development Zone,

Cixi City, Zhejiang Province, China

Zip code: 315303

Switchboard: +86 574-63288158

Fax: +86 574-63288170

E-mail:supucontact@supu.cn

Service Hotline: 400-626-6336



Wechat