



Product Type: Fixed terminal

Product Name:MC-TE3.81H24C-0001

Product Description: Pitch:3.81mm Rated Voltage : 160V Rated Current:12A Connection method : Screw connection colour : customizable

Product Size



Parameters

 SUPU ID	MC-TE3.81H24C-0001
 Pitch	3.81
 Number of levels	Single layer
 Number of connections	24

☞ Connection method	Screw connection
☞ Protection Level	IP20
☞ Operating temperature range	-40~+105°C
☞ Insulation material	PA66
☞ Insulation material group	I
☞ Contact material	Copper alloy
☞ Contact plating	Sn,Plated
☞ Color	Green/Black/Blue/Grey/Orange/Red

Technical data

☞ IEC Rated Current	12A
☞ IEC Rated Voltage	160V
☞ Overvoltage category	III/III/ II
☞ Degree of pollution	3 2 2
☞ Rated impulse voltage	2.5KV 2.5KV 2.5KV
☞ UL Rated Current	12A - 10A
☞ UL Rated Voltage	300V - 300V
☞ Conductor cross section rigid	0.2~1.5mm ²
☞ Conductor cross section flexible	0.2~1.5mm ²
☞ Conductor cross section flexible,with furrule	0.2~1.0mm ²
☞ Locking screw Specification	M2
☞ Locking screw torque	0.2N.m
☞ Fixed Screw Specification	-
☞ Stripping length	5-6mm

☞ Order No

MC-TE3.81H24C-0001

Ningbo SUPU Electronics Co., Ltd.

Address: No. 150, Xinxing 4th Road, High-tech Industrial Development Zone,
Cixi City, Zhejiang Province, China

Zip code: 315303

Switchboard: +86 574-63288158

Fax: +86 574-63288170

E-mail:supucontact@supu.cn

Service Hotline: 400-626-6336



Wechat

Date:2025-10-28 08:15

The right to modify data belongs to SUPU.