





Product Type: Plug-in terminal-Socket

Product Name:478474-010

Product Description: Pitch:7.62mm Rated

Voltage : 500V Rated Current:16A colour : orange

## Product Size



## Parameters

|                                                                                                    |              |
|----------------------------------------------------------------------------------------------------|--------------|
|  SUPU ID          | 4784614-010  |
|  Pitch            | 7.62         |
|  Number of levels | Single layer |

|                               |              |
|-------------------------------|--------------|
| ☞ Number of connections       | 14           |
| ☞ Connection method           | -            |
| ☞ Protection Level            | IP20         |
| ☞ Operating temperature range | -40~+105°C   |
| ☞ Insulation material         | PA66         |
| ☞ Insulation material group   | I            |
| ☞ Contact material            | Copper alloy |
| ☞ Contact plating             | Sn,Plated    |
| ☞ Color                       | Orange       |

## Technical data

|                                                 |                   |
|-------------------------------------------------|-------------------|
| ☞ IEC Rated Current                             | 500V              |
| ☞ IEC Rated Voltage                             | 16A               |
| ☞ Overvoltage category                          | III III II        |
| ☞ Degree of pollution                           | 3 2 2             |
| ☞ Rated impulse voltage                         | 4.0KV 4.0KV 4.0KV |
| ☞ UL Rated Current                              | 15A - 10A         |
| ☞ UL Rated Voltage                              | 300V - 300V       |
| ☞ Conductor cross section rigid                 | -                 |
| ☞ Conductor cross section flexible              | -                 |
| ☞ Conductor cross section flexible,with furrule | -                 |
| ☞ Locking screw Specification                   | -                 |
| ☞ Locking screw torque                          | -                 |
| ☞ Fixed Screw Specification                     | -                 |

|                     |       |
|---------------------|-------|
| 固定螺钉扭矩              | -     |
| Stripping length    | -     |
| Use group           | B/C/D |
| Rated cross section | -     |

Commercial data

|          |             |
|----------|-------------|
| Order No | 4784614-010 |
|----------|-------------|

Ningbo SUPU Electronics Co., Ltd.  
 Address: No. 150, Xinxing 4th Road, High-tech Industrial Development Zone,  
 Cixi City, Zhejiang Province, China  
 Zip code: 315303  
 Switchboard: +86 574-63288158  
 Fax: +86 574-63288170  
 E-mail:supucontact@supu.cn  
 Service Hotline: 400-626-6336



Wechat