


Product Type: Screw terminal

## Product Name:335991

Product Description: Connection method:Screw connection,IEC Rated current:25A,IEC Rated Voltage:1000V,Number of connections:2,Number of levels : 1,Rated cross section:8-1/0AWG

### Product Size



### Parameters

<input checked="" type="checkbox"/> SUPU ID	335991
<input checked="" type="checkbox"/> Width	16mm
<input checked="" type="checkbox"/> Number of levels	1
<input checked="" type="checkbox"/> Number of connections	2

<input type="checkbox"/> Connection method	Screw connection
<input type="checkbox"/> Protection Level	IP20
<input type="checkbox"/> Insulation material	PA66
<input type="checkbox"/> Insulation material group	I
<input type="checkbox"/> Contact material	Copper
<input type="checkbox"/> Contact plating	Sn,Plated
<input type="checkbox"/> Ambient temperature (operation)	-40°C~105°C
<input type="checkbox"/> Ambient temperature (assembly)	-5°C~70°C
<input type="checkbox"/> Ambient temperature (storage)	-25°C~60°C
<input type="checkbox"/> Permissible humidity (storage/transport)	30%~70%
<input type="checkbox"/> Product type	Terminal block of side-entry

## Technical data

<input type="checkbox"/> IEC Rated Current	25A
<input type="checkbox"/> IEC Rated Voltage	1000V
<input type="checkbox"/> Overvoltage category	III
<input type="checkbox"/> Degree of pollution	3
<input type="checkbox"/> Rated impulse voltage	8kV
<input type="checkbox"/> UL Rated Current	150A
<input type="checkbox"/> UL Rated Voltage	600V
<input type="checkbox"/> Conductor cross section rigid	10-35mm <sup>2</sup>
<input type="checkbox"/> Conductor cross section flexible	10-35mm <sup>2</sup>
<input type="checkbox"/> Conductor cross section flexible,with ferrule	10-35mm <sup>2</sup>
<input type="checkbox"/> Locking screw Specification	M6

<input type="checkbox"/> Locking screw torque	3-3.5N.m
<input type="checkbox"/> Fixed Screw Specification	/
<input type="checkbox"/> 固定螺钉扭矩	/
<input type="checkbox"/> Stripping length	16-17mm
<input type="checkbox"/> Use group	B/C
<input type="checkbox"/> Rated cross section	8-1/0AWG
<input type="checkbox"/> UL Rated Current	150A
<input type="checkbox"/> UL Rated Current	600V

## Commercial data

<input type="checkbox"/> Order No	335991
-----------------------------------	--------

### Ningbo SUPU Electronics Co., Ltd.

Address: No. 150, Xinxing 4th Road, High-tech Industrial Development Zone,

Cixi City, Zhejiang Province, China


Zip code: 315303

Switchboard: +86 574-63288158

Fax: +86 574-63288170

E-mail:supucontact@supu.cn

Service Hotline: 400-626-6336



---

Date:2026-04-30 03:01

The right to modify data belongs to SUPU.