




Product Type: Fixed terminal


Product Name:MC-TF7.62H09C-0001

Product Description: Pitch:7.62mm Rated

Voltage : 630V Rated Current:24A Connection

method : Screw connection colour : customizable

Product Size



Parameters

⌘ SUPU ID	MC-TF7.62H09C-0001	
⌘ Pitch	7.62	
⌘ Number of levels	Single layer	
⌘ Number of connections	9	
⌘ Connection method	Screw connection	
⌘ Protection Level	IP20	
⌘ Operating temperature range	-40~+105°C	
⌘ Insulation material	PA66	

☞ Insulation material group	I
☞ Contact material	Copper alloy
☞ Contact plating	Sn,Plated
☞ Color	Green/Black/Blue/Grey/Orange/Red

Technical data

☞ IEC Rated Current	24A
☞ IEC Rated Voltage	630V
☞ Overvoltage category	III/III/ II
☞ Degree of pollution	3 2 2
☞ Rated impulse voltage	6.0KV 6.0KV 6.0KV
☞ UL Rated Current	15A - 10A
☞ UL Rated Voltage	300V - 300V
☞ Conductor cross section rigid	0.2-2.5mm ²
☞ Conductor cross section flexible	0.2-2.5mm ²
☞ Conductor cross section flexible,with furrule	0.2-2.5mm ²
☞ Locking screw Specification	M3
☞ Locking screw torque	0.5N.m
☞ Fixed Screw Specification	-
☞ Stripping length	7-8mm

Commercial data

☞ Order No	MC-TF7.62H09C-0001
------------	--------------------

Ningbo SUPU Electronics Co., Ltd.

Address: No. 150, Xinxing 4th Road, High-tech Industrial Development Zone,
Cixi City, Zhejiang Province, China

Zip code: 315303

Switchboard: +86 574-63288158

Fax: +86 574-63288170

E-mail:supucontact@supu.cn

Service Hotline: 400-626-6336



Wechat

Date:2025-12-14 14:32

The right to modify data belongs to SUPU.