



Product Type: Fixed terminal

**Product Name:MC-TI3.5H06P-  
BK-1600**

Product Description: Pitch:3.5mm Rated  
Voltage : 200V Rated Current:17.5A Connection  
method : Push in connection  
colour : customizable

Product Size



Parameters

|                               |                      |              |
|-------------------------------|----------------------|--------------|
| ⌘ SUPU ID                     | MC-TI3.5H06P-BK-1600 |              |
| ⌘ Pitch                       |                      | 3.5          |
| ⌘ Number of levels            |                      | Single layer |
| ⌘ Number of connections       |                      | 6            |
| ⌘ Connection method           | Push in connection   |              |
| ⌘ Protection Level            |                      | IP20         |
| ⌘ Operating temperature range |                      | -40~+130°C   |
| ⌘ Insulation material         |                      | PA66         |

|                             |                                  |
|-----------------------------|----------------------------------|
| ☞ Insulation material group | I                                |
| ☞ Contact material          | Copper alloy                     |
| ☞ Contact plating           | Sn,Plated                        |
| ☞ Color                     | Green/Black/Blue/Grey/Orange/Red |

## Technical data

|                                                 |                        |
|-------------------------------------------------|------------------------|
| ☞ IEC Rated Current                             | 17.5A                  |
| ☞ IEC Rated Voltage                             | 200V                   |
| ☞ Overvoltage category                          | III/III/ II            |
| ☞ Degree of pollution                           | 3 2 2                  |
| ☞ Rated impulse voltage                         | 2.5KV 2.5KV 2.5KV      |
| ☞ UL Rated Current                              | 12A - 10A              |
| ☞ UL Rated Voltage                              | 300V - 300V            |
| ☞ Conductor cross section rigid                 | 0.2-1.5mm <sup>2</sup> |
| ☞ Conductor cross section flexible              | 0.2-1.5mm <sup>2</sup> |
| ☞ Conductor cross section flexible,with furrule | 0.2-1.5mm <sup>2</sup> |
| ☞ Locking screw Specification                   | -                      |
| ☞ Locking screw torque                          | -                      |
| ☞ Fixed Screw Specification                     | -                      |
| ☞ Stripping length                              | 8-9mm                  |

## Commercial data

|            |                      |
|------------|----------------------|
| ☞ Order No | MC-TI3.5H06P-BK-1600 |
|------------|----------------------|

## Ningbo SUPU Electronics Co., Ltd.

Address: No. 150, Xinxing 4th Road, High-tech Industrial Development Zone,  
Cixi City, Zhejiang Province, China

Zip code: 315303

Switchboard: +86 574-63288158

Fax: +86 574-63288170

E-mail:supucontact@supu.cn

Service Hotline: 400-626-6336



Wechat

---

Date:2025-12-14 12:29

The right to modify data belongs to SUPU.