



Product Description: Pitch: 5.08mm Rated  
Voltage : 320V Rated Current: 8A  
colour : customizable

## Parameters

3

|                               |                                  |
|-------------------------------|----------------------------------|
| ☞ Connection method           | -                                |
| ☞ Protection Level            | IP20                             |
| ☞ Operating temperature range | -40~+105°C                       |
| ☞ Insulation material         | PA66                             |
| ☞ Insulation material group   | I                                |
| ☞ Contact material            | Copper alloy                     |
| ☞ Contact plating             | Sn,Plated                        |
| ☞ Color                       | Green/Black/Blue/Grey/Orange/Red |

## Technical data

|                         |                   |
|-------------------------|-------------------|
| ☞ IEC Rated Current     | 320V              |
| ☞ IEC Rated Voltage     | 8A                |
| ☞ Overvoltage category  | III III II        |
| ☞ Degree of pollution   | 3 2 2             |
| ☞ Rated impulse voltage | 4.0KV 4.0KV 4.0KV |
| ☞ UL Rated Current      | 8A - 8A           |
| ☞ UL Rated Voltage      | 300V - 300V       |
| ☞ Use group             | B/C/D             |

## Commercial data

|            |                   |
|------------|-------------------|
| ☞ Order No | MC-PD5.08V03-0001 |
|------------|-------------------|

Ningbo SUPU Electronics Co., Ltd.

Address: No. 150, Xinxing 4th Road, High-tech Industrial Development Zone,  
Cixi City, Zhejiang Province, China

Zip code: 315303

Switchboard: +86 574-63288158

Fax: +86 574-63288170

E-mail:supucontact@supu.cn

Service Hotline: 400-626-6336



Wechat

---

Date:2026-02-16 21:26

The right to modify data belongs to SUPU.