

Product Type: Plug-in terminal-Plug

Product Name:MC-RB7.62H08C-0001



Product Description: Pitch:7.62mm Rated Voltage : 630V Rated Current:18A Connection method : Screw connection colour : customizable

## Product Size



## Parameters

|                         |                    |
|-------------------------|--------------------|
| ⌘ SUPU ID               | MC-RB7.62H08C-0001 |
| ⌘ Pitch                 | 7.62               |
| ⌘ Number of levels      | single layer       |
| ⌘ Number of connections | 8                  |

|                             |                                  |
|-----------------------------|----------------------------------|
| Connection method           | Screw connection                 |
| Protection Level            | IP20                             |
| Operating temperature range | -40~+105°C                       |
| Insulation material         | PA66                             |
| Insulation material group   | I                                |
| Contact material            | Copper alloy                     |
| Contact plating             | Sn,Plated                        |
| Color                       | Green/Black/Blue/Grey/Orange/Red |

### Technical data

|                                               |                        |
|-----------------------------------------------|------------------------|
| IEC Rated Current                             | 18A                    |
| IEC Rated Voltage                             | 630V                   |
| Overvoltage category                          | III/III/ II            |
| Degree of pollution                           | 3 2 2                  |
| Rated impulse voltage                         | 6.0KV 6.0KV6.0KV       |
| UL Rated Current                              | 15A - 10A              |
| UL Rated Voltage                              | 300V - 300V            |
| Conductor cross section rigid                 | 0.2-2.5mm <sup>2</sup> |
| Conductor cross section flexible              | 0.2-2.5mm <sup>2</sup> |
| Conductor cross section flexible,with furrule | 0.2-2.5mm <sup>2</sup> |
| Locking screw Specification                   | M3                     |
| Locking screw torque                          | 0.5N.m                 |
| Fixed Screw Specification                     | -                      |
| 固定螺钉扭矩                                        | -                      |

|                       |          |
|-----------------------|----------|
| ☞ Stripping length    | 7~8mm    |
| ☞ Use group           | B/C/D    |
| ☞ Rated cross section | 24~12AWG |

## Commercial data

|            |                    |
|------------|--------------------|
| ☞ Order No | MC-RB7.62H08C-0001 |
|------------|--------------------|

## Ningbo SUPU Electronics Co., Ltd.

Address: No. 150, Xinxing 4th Road, High-tech Industrial Development Zone,

Cixi City, Zhejiang Province, China

Zip code: 315303

Switchboard: +86 574-63288158

Fax: +86 574-63288170

E-mail:supucontact@supu.cn

Service Hotline: 400-626-6336



Wechat